

TRELLOIL S

OIL & GAS

Oil and petroleum/Suction and discharge applications

Suction and discharge of petroleum products with aromatic content up to 50% in all industrial applications.

Road tanker equipment for oil and petrol deliveries.

Advantages

- Easily cut to length and fitted with couplings.
- Light weight and flexible, even at cold temperature.
- Dissipation of static electricity ensured by contact of built-in wire with the coupling.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant NBR/SBR, black, fabric impression.

Temperature range: -30°C to +80°C.

Electrical properties: built-in conductive wire



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
25.0	5.25 ±0.5	35.5 ±1.0	10	30	0.9	50	0.83	20 - 40	
32.0	5.25 ±0.5	42.5 ±1.0	10	30	0.9	65	1.01	20 - 40	
35.0	5.25 ±0.5	45.5 ±1.0	10	30	0.9	70	1.07	20 - 40	
38.0	5.75 ±0.5	49.5 ±1.0	10	30	0.9	80	1.23	20 - 40	
40.0	5.75 ±0.5	51.5 ±1.0	10	30	0.9	85	1.29	20 - 40	
45.0	6.0 ±0.5	57.0 ±1.0	10	30	0.9	90	1.50	20 - 40	
50.0	6.5 ±0.75	63.0 ±1.5	10	30	0.9	125	1.83	20 - 40	
55.0	6.5 ±0.75	68.0 ±1.5	10	30	0.9	145	1.96	20 - 40	
60.0	6.5 ±0.75	73.0 ±1.5	10	30	0.9	150	2.21	20 - 40	
63.0	6.5 ±0.75	76.0 ±1.5	10	30	0.9	160	2.29	20 - 40	
70.0	7.5 ±0.75	85.0 ±1.5	10	30	0.9	210	2.85	20 - 40	
75.0	7.5 ±0.75	90.0 ±1.5	10	30	0.9	225	3.00	20 - 40	
80.0	7.5 ±0.75	95.0 ±1.5	10	30	0.9	280	3.20	20 - 40	
89.0	7.5 ±0.75	104.0 ±1.5	10	30	0.9	335	3.57	20 - 40	
100.0	7.5 ±0.75	115.0 ±1.6	10	30	0.9	400	3.95	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

