



PUMPADUKT L

OIL & GAS

Oil and petroleum/Suction and discharge applications

Suction and discharge of petroleum products with aromatics up to 50%.
Equipment of road tank trucks for oil and petrol deliveries and their loading/unloading bays.

Advantages

- A highly light weight and flexible hose for easy handling. The corrugated cover allows extreme bendings.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant CR, black, corrugated, fabric impression.

Temperature range: -40°C to +100°C.

Electrical properties: conductive tube, $R < 10^6 \Omega / \text{lg}$.

Standard/Approval:

TRbF 131 Teil 2, EN 1761.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
50.0 ±0.6	8.0	66.0 ±1.2	10	40	0.9	100	2.01	20 - 40*	
75.0 ±0.6	8.0	91.0 ±1.2	10	40	0.9	150	3.18	40	
100.0 ±0.6	8.0	116.0 ±1.6	10	40	0.9	200	3.99	20 - 40*	

Tolerance on length: ±1% (ISO 1307 Standard).

* Stock item in Germany (Mettmann).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding



and embossed: TRELLEBORG - PUMPADUKT L - NBR 1 - EN 1761:1999 - SD - ND - WP 10bar - Ω/T - month/year - batch number