

PARATUB

PROCESSING EQUIPMENT

Chemical and corrosive products/Transfer

Discharge under pressure or gravity flow of corrosive products such as acids and alkalis.

Advantages

- This tube can be cut to length as required.
- Flexible and easy to handle.
- Excellent resistance to low temperatures.

Technical description

Inner tube: chemical resistant NR, beige, smooth inside, fabric impression outside.

Temperature range: -40°C to +70°C.

Electrical properties: non conductive.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Weight kg/m	Length m	Notes
15.0	-0/+1	5.0	25.0 ±1	1	0.34	20
20.0	-0/+1	5.0	30.0 ±1	1	0.43	20 - 40
25.0	-0/+1	5.0	35.0 ±1	1	0.51	20 - 40
30.0	-0/+1	5.0	40.0 ±1	1	0.59	20 - 40
35.0	-0/+1	5.0	45.0 ±1	1	0.67	20 - 40
40.0	-0/+1	5.0	50.0 ±1	1	0.76	20 - 40
50.0	-0/+1	5.0	60.0 ±1	1	0.92	20 - 40
60.0	-0/+1	5.0	70.0 ±1	1	1.09	20 - 40
80.0	-0/+1	7.5	95.0 ±1	1	2.12	20 - 40

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

No branding.