



PARKING®

Application

The PARKING® compressed air hose is the reliable and safe hose for heavy duty service for quarrying, above and underground construction, for use on compressed air tools or compressors, industrial applications, for the steel industry, shipyards, petrol stations and body workshops.

Marking

6 blue stripes on black cover

Description

- › Black, non porous and smooth SBR lining
- › Reinforcements: synthetic fibres
- › Black, smooth SBR/EPDM cover, resistant to ozone, weather, UV and abrasion
- › Working pressure up to 20 bar / 290 psi
- › Temperature range up to +65°C / +149°F, short term up to +80°C / +176°F
- › Release agent- and fat-free, free from any product harmful to lacquer

Technical data

nominal width zoll/inch	inner-Ø mm	wall thickness mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/m
				bar	psi	bar	psi		
1/4	6	3.5	25	20	290	60	870	60	170
1/4	6	3.5	50	20	290	60	870	60	170
1/3	8	3.5	25	20	290	60	870	80	200
1/3	8	3.5	50	20	290	60	870	80	200
3/8	10	3.5	25	20	290	60	870	100	250
3/8	10	3.5	50	20	290	60	870	100	250
1/2	13	4.3	20	20	290	60	870	130	350
1/2	13	4.3	40	20	290	60	870	130	350
3/4	19	5.5	20	20	290	60	870	190	580
3/4	19	5.5	40	20	290	60	870	190	580

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

