



TRIX® Paint spray hose NBR

for easy and safe varnishing

Application

The TRIX® Paint spray hose NBR is the ideal product for paint shops, dockyards, painters and many other industrial applications. It is highly flexible, non-kinking, non-buckling, and its smooth lining is especially suitable for conveying alkyd resin lacquers, latex paint, spirit lacquers and polyester lacquers (2 components). Further information concerning resistance to paints, lacquers, cleaning agents and solvents is available on request.

Marking

6 grey, axially applied stripes on black cover "Continental ContiTech TRIX® FARBSPRITZ / PAINT SPRAY NBR DN 9 PN 25 BAR / 363 PSI R < 10⁶ Ω Made in Germany"

Description

- › Black, non-porous and smooth NBR lining
- › Reinforcements: synthetic fibres
- › Black, smooth NBR-cover, resistant to ozone, weather and UV
- › Working pressure up to 25 bar / 363 psi
- › Temperature range from -30°C up to +80°C / -22°F up to +176°F
- › Release agent- and fat-free, free from any product harmful to lacquer
- › Length independently electrically conductive, R < 10⁶ Ω

Technical data

nominal width zoll/inch	inner-Ø mm	wall thickness mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/m
				bar	psi	bar	psi		
1/4	6	3.5	40	25	363	100	1450	25	170
3/8	9	3.5	40	25	363	100	1450	35	230
7/16	11	4.0	40	25	363	100	1450	45	260

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

