

Continental ContiTech TEERSPRITZ / TARSPRAY DN 19 PN 16 BAR / 232 PSI Made in Germany

# CONTI® Tar spray hose

For use in road construction

## Application

CONTI® Tar spray hose is the perfect equipment hose the use of bitumen and tar equipment in roadmaking. The hard-wearing NBR lining and cover and the selected reinforcement materials will ensure a long service life. The hose is flexible and due to its construction electrically conductive.

## Marking

"Continental ContiTech TEERSPRITZ / TARSPRAY DN 19 PN 16 BAR/ 232 PSI Made in Germany" on grey cover

## Description

- › Black, smooth NBR lining
- › Reinforcements:
- › Black, fabric patterned NBR cover, resistant to ozone, weather, UV and abrasion
- › Working pressure up to 16 bar /232 psi
- › Burst pressure > 80 bar / 1.160 psi
- › Temperature range from -25°C up to +180°C / -13°F up to +356°F
- › Electrically conductive

## Technical data

nominal width zoll/inch	inner-Ø mm	wall thickness mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/m
				bar	psi	bar	psi		
3/4	19	6.3	>2	16	232	80	1160	200	778

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

