

## High-Pressure Slimline Couplers

Slimline couplers are designed to be used **ONLY** for high pressure waterjetting applications, such as tube bundle cleaning.

Part Number	Description	Max Working Pressure
HCSL-HF4-LL	1/4" HP Female Slimline Coupler Left x Left* 0.445" OD	2,760 bar / 40,000 psi
HCSL-HF4-LR	1/4" HP Female Slimline Coupler Left x Right* 0.445" OD	2,760 bar / 40,000 psi
HCSL-HF4-RR	1/4" HP Female Slimline Coupler Right x Right* 0.445" OD	2,760 bar / 40,000 psi
HCSL-HF6-LL	3/8" HP Female Slimline Coupler Left x Left* 0.562" OD	2,760 bar / 40,000 psi
HCSL-HF6-LR	3/8" HP Female Slimline Coupler Left x Right* 0.562" OD	2,760 bar / 40,000 psi
HCSL-HF6-RR	3/8" HP Female Slimline Coupler Right x Right* 0.562" OD	2,760 bar / 40,000 psi
HCSL-HF9-LL	9/16" HP Female Slimline Coupler Left x Left* 0.750" OD	2,760 bar / 40,000 psi
HCSL-HF9-LR	9/16" HP Female Slimline Coupler Left x Right* 0.750" OD	2,760 bar / 40,000 psi
HCSL-HF9-RR	9/16" HP Female Slimline Coupler Right x Right* 0.750" OD	2,760 bar / 40,000 psi



\* Designates Left Hand Thread or Right Hand Thread