

Quick Disconnect Female Couplers with Check Valve

Part Number	Description	Max Working Pressure
SPC600-0-M9	Coupler with Check Valve x 9/16"-18 Type M	2,068 bar / 30,000 psi
SPC600-0-M12	Coupler with Check Valve x 3/4"-16 Type M	2,068 bar / 30,000 psi
SPC600-0-M16	Coupler with Check Valve x 1"-12 Type M	2,068 bar / 30,000 psi
SPC600-0-MJ4	Coupler with Check Valve x 1/4" JIC Male	690 bar / 10,000 psi
SPC600-0-MJ6	Coupler with Check Valve x 3/8" JIC Male	690 bar / 10,000 psi
SPC600-0-MJ8	Coupler with Check Valve x 1/2" JIC Male	690 bar / 10,000 psi
SPC600-0-NM4	Coupler with Check Valve x 1/4" NPT Male	1,035 bar / 15,000 psi
SPC600-0-NM6	Coupler with Check Valve x 3/8" NPT Male	1,035 bar / 15,000 psi
SPC600-0-NM8	Coupler with Check Valve x 1/2" NPT Male	1,035 bar / 15,000 psi
SPC600-0-NF4	Coupler with Check Valve x 1/4" NPT Female	1,035 bar / 15,000 psi
SPC600-0-NF6	Coupler with Check Valve x 3/8" NPT Female	1,035 bar / 15,000 psi
SPC600-0-NF8	Coupler with Check Valve x 1/2" NPT Female	1,035 bar / 15,000 psi
SPC600-0-MP4	Coupler with Check Valve x 1/4" MP Male	1,380 bar / 20,000 psi
SPC600-0-MP6	Coupler with Check Valve x 3/8" MP Male	1,380 bar / 20,000 psi
SPC600-0-MP9	Coupler with Check Valve x 9/16" MP Male	1,380 bar / 20,000 psi
SPC600-0-HP4	Coupler with Check Valve x 1/4" HP Male	2,068 bar / 30,000 psi
SPC600-0-HP6	Coupler with Check Valve x 3/8" HP Male	2,068 bar / 30,000 psi
SPC600-0-HP9	Coupler with Check Valve x 9/16" HP Male	2,068 bar / 30,000 psi
SPC600-0-X13	Coupler with Check Valve x Low Angle Male	2,068 bar / 30,000 psi

