

## Quick Disconnect Male Nipples without Check Valve

Part Number	Description	Max Working Pressure
SPC600-I-M9	Nipple without Check Valve x 9/16"-18 Type M	2,068 bar / 30,000 psi
SPC600-I-M12	Nipple without Check Valve x 3/4"-16 Type M	2,068 bar / 30,000 psi
SPC600-I-M16	Nipple without Check Valve x 1"-12 Type M	2,068 bar / 30,000 psi
SPC600-I-MJ4	Nipple without Check Valve x 1/4" JIC Male	690 bar / 10,000 psi
SPC600-I-MJ6	Nipple without Check Valve x 3/8" JIC Male	690 bar / 10,000 psi
SPC600-I-MJ8	Nipple without Check Valve x 1/2" JIC Male	690 bar / 10,000 psi
SPC600-I-NM4	Nipple without Check Valve x 1/4" NPT Male	1,035 bar / 15,000 psi
SPC600-I-NM6	Nipple without Check Valve x 3/8" NPT Male	1,035 bar / 15,000 psi
SPC600-I-NM8	Nipple without Check Valve x 1/2" NPT Male	1,035 bar / 15,000 psi
SPC600-I-NF4	Nipple without Check Valve x 1/4" NPT Female	1,035 bar / 15,000 psi
SPC600-I-NF6	Nipple without Check Valve x 3/8" NPT Female	1,035 bar / 15,000 psi
SPC600-I-NF8	Nipple without Check Valve x 1/2" NPT Female	1,035 bar / 15,000 psi
SPC600-I-MP4	Nipple without Check Valve x 1/4" MP Male	1,380 bar / 20,000 psi
SPC600-I-MP6	Nipple without Check Valve x 3/8" MP Male	1,380 bar / 20,000 psi
SPC600-I-MP9	Nipple without Check Valve x 9/16" MP Male	1,380 bar / 20,000 psi
SPC600-I-HP4	Nipple without Check Valve x 1/4" HP Male	2,068 bar / 30,000 psi
SPC600-I-HP6	Nipple without Check Valve x 3/8" HP Male	2,068 bar / 30,000 psi
SPC600-I-HP9	Nipple without Check Valve x 9/16" HP Male	2,068 bar / 30,000 psi
SPC600-I-XI3	Nipple without Check Valve x Low Angle Male	2,068 bar / 30,000 psi

